

Question # 10 of 10 (**Start time: 10:36:04 PM, 28 June 2024**)

Which function is automatically called in C++ if we do not define it in a class?

Select the correct option

☐	Inline function
☒	Default Constructor
☐	Default and Parametrized Constructor
☐	Parametrized Constructor



Question # 9 of 10 (Start time: 10:35:29 PM, 28 June 2024)

What will be the output of the following code?

```
void sampleFunction(int = 5,float = 4.1, char = 'A');  
int main(){  
    sampleFunction(50,3.2);  
}  
  
void sampleFunction(int one,float two ,char three) {  
    cout << one << " , " << two << " , " << three;  
}
```

Select the correct option

☐	5, 4.1, A
☐	50, 4.1, A
☐	5, 3.2, A
☒	50, 3.2, A

Click



CS201P - Introduction to Programming (Practical) (Regular Quiz 3)

Quiz Start Time: 10:31

Question # 8 of 10 (Start time: 10:34:54 PM, 28 June 2024)

In C++, the name of the _____ is the same as that of a class with a preceding tilde (~) sign.

Select the correct option

Reload

☐	Friend function
☒	Destructor
☐	Utility function
☐	Constructor

Click to Save Answer & Move to

Question # 7 of 10 (**Start time: 10:34:23 PM, 28 June 2024**)

In C++, when accessing files randomly, which function is used to get current pointer position inside a file?

Select the correct option

☒	tellg()
☐	tellp()
☐	seekg()
☐	seekp()

[Click to Save](#)

Question # 6 of 10 (Start time: 10:33:59 PM, 28 June 2024)

Total Marks: 1

Functions **seekg ()** and **seekp ()** require an argument of type ____ to let them know how many bytes to move forward or backward.

Select the correct option



Reload Math Equations



float



int



double



long

Click to Save Answer & Move to Next Question

**Question # 5 of 10 (Start time: 10:33:15 PM, 28 June 2024)**

In C++, which operator is used while accessing through the pointer to structure?

Select the correct option

☒	->
☐	&
☐	-
☐	=



vulms.vu.edu.pk/



1

**CS201P - Introduction to Programming (Practical) (Regular Quiz 3)****Question # 4 of 10 (Start time: 10:32:45 PM, 28 June 2024)**

Dynamic memory allocation uses memory from the _____.

Select the correct option

☐	Stack
☒	Heap
☐	Mulit-dimensional Array
☐	Array

**CS201P - Introduction to Programming (Practical) (Regular Quiz 3)****Question # 3 of 10 (Start time: 10:32:16 PM, 28 June 2024)**

What would be the output of the following statement?
`c = 13 % 2;`

Select the correct option

☐	0
☒	1
☐	3
☐	2



Question # 2 of 10 (Start time: 10:31:48 PM, 28 June 2024)

Which of the following is not true about Destructor?

Select the correct option

☐	Destructors cannot be overloaded.
☒	Destructors cannot be used for memory manipulation.
☐	Destructors don't return a value.
☐	Destructors take no arguments



vulms.vu.edu.pk/



1



CS201P - Introduction to Programming (Practical) (Regular Quiz 3)

Question # 1 of 10 (Start time: 10:31:11 PM, 28 June 2024)

In C++, which operator is used to access the data members of the class?

Select the correct option

☐	Not
☐	Plus
☒	Dot
☐	And