VISIT ANY MORE SOLUTIONS

www.vuanswer.com

CS201 SOLVED QUIZ 1

Effort by Sarim (VUANSWER)

Question # 1

< and > both are_____operators.

Arithmetic
Relational
Logical
Mathematical

Question # 2

Find out the logical error in following lines of code. If (x = 10) cout "x is 10";

10 should be enclosed in quotations
There is no semicolon at the end of if condition
Assignment operator should not be used for Comparison
Variable x should not be inside parenthesis

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

Question # 3

What will be the result of the expression j = i++; if initially j = 0 and i = 5?

0
5
6
4

Question # 4

Default mechanism of calling a function by passing it array is call by_____and in case of passing variable is call by _____.

Reference, Reference
Reference, value
Value, Reference
Value, Value

Question # 5

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

When the break statement is encountered in a loop's body, it transfers the control_____from the current loop.

Inside
Outside
To break statement
To continue statement

Question # 6

_____statement is used to terminate the processing of a particular case and exit from switch structure.
If
Goto
Break
Continue

Question # 7

If we pass more than one arguments to a function then they are separated by_____.

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

Comma, Lecture 9

Semicolon;

Colon:

Brackets ()

Question # 8

What will be the value of the variable output **in the given piece of code? double output = 0; output = (2 + 2) * 4 + 2 / (4 – 2);**

15
17
12
1

Question # 9

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout statement?

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

2
2.1
2.06
2.07

Question # 10

_____will be used for clarity and to force the order of evaluation in an expression.
" "
() PG32
' '
[ ]

Question # 11

What will be the size of following array? int arr[29];

0
30 PAGE 105-106

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

29

28

Question # 12

If a function has not been declared before its definition, It is logical error

syntax error LECTURE NO 9
logical Error
run time error
none of these

Question # 13

When the break statement is encountered in a loop‟s body, it transfers the control___from the current loop.

Inside

Outside By using break the loop will terminate.

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

To break statement

To continue statement

Question # 14

When we access a multidimensional array, each array index is surrounded by_.

Single quotes ' '

Double quotes " "

Brackets[] Lecture 11

None of the given

Question # 14

char name [] = “Hello World” ; In the above statement, a memory of____characterswill be allocated

12 Lecture 12

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

10

11

13

Question # 15

A variable declared within a code block becomes___variable for that block.

Static

Integer

Local Lecture 9

Global

Question # 16

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

When the if statement consists of more than one statement then enclosing these statement in braces is _____.

Compulsory
Optional
Not required
Relevant

Question # 17

Characters of a string stored in an array can be accessed directly using array____.

Manipulation

Superscript

Subscript Page No 123

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

Postscript

Question # 18

A variable declared within a code block becomes___variable for that block.

Static

Integer

Local Lecture 9

Global

Question # 19

The data type before a function name represents its,

Return Type

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

Function data

Function arguments

Function name

Question # 19

From following; which one is the correct syntax of an array initialize: Array size is 10 andit is of double data type to value 0?

arr[10] = {0.0};

double arr[10]= 0.0;

Double arr[10] = {0.0}; Lecture 12

double arr[] = 0.0;

Question # 20

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VISIT ANY MORE SOLUTIONS

www.vuanswer.com

In C/C++, by default arguments are passed by_to a function.

Value Lecture 9

Reference

Prototype

None of the given

Question # 21

By default, the starting index of an array in C++ is

0 Lecture 11

2

1

-1

JOIN OUR WHATSAPP

https://chat.whatsapp.com/CD2snTdbdZt7YgXQNUAoOQ

LIKE OUR FACEBOOK PAGE

https://www.facebook.com/vuanswer

VUANSWER.COM